PJ358

LIGHT, BRIGHT AND PORTABLE PROJECTOR

WITH KEYSTONE CORRECTION

Portable and multifunctional.

The ViewSonic® PJ358 XGA projector weighs in at only 1.78kg but DELIVERS POWERFUL PRESENTATIONS WITH NATIVE 1024×768 RESOLUTION AND AN AMAZING 2,200 LUMENS. Professional presenters will appreciate the full feature set including dual RGB inputs and USB storage support that allow you to connect two PCs or PC-Less Presentation. The PJ358 SETS UP EASILY WITH ITS ONE-TOUCH SET UP BUTTON AND DISPLAYS THE PERFECT IMAGE in virtually any setting thanks to digital keystone correction, manual zoom and focus. The included remote control with mouse makes it easy to deliver a dynamic presentation that puts you in the best possible light.

SRS WOW

DELIVER BRIGHT, POWERFUL PRESENTATIONS

> **Bright in virtually any setting with 2,200 lumens**
Packs 2,200 lumens in just 1.78kg. It`s the bright choice for mobile presenters.

> **Ultimate video source flexibility**
Connect a computer or add a video source for dynamic meetings and presentations.

> **Advanced video features**
Progressive scan and 3:2 pull down for superior video performance.

> **Whisper-mode extends lamp life & low noise 30dB**
Extend the life of your lamp up to 4,000 hours** and reduce noise output.

> **6 default picture mode for different environment usage**
Dynamic, Cinema, Normal , Whiteboard, Board(Black), and Daylight Mode.

> **Keylock and security slot for anti-theft**
Design to avoid a mischief and touching.

> **Off To Go feature**
Allow to unplug projector power cable without traditional turn off procedure.

> **Short Throw Feature**
Projection 60" image at 1.5m

MORE THAN 2000 AWARDS

VIEWSONIC
PRODUCTS, PROGRAMS, AND SERVICES

ViewSonic®
See the difference™

PJ358

LIGHT, BRIGHT AND PORTABLE PROJECTOR WITH KEYSTONE CORRECTION

Optional Accessories

- Replacement lamp.....RLC-027

(a) Screen size (diagonal)		4 : 3 screen							
		(b) Projection distance				(c) Screen height			
		min.		max.		down		up	
inch	m	m	inch	m	inch	cm	inch	cm	inch
60	1.5	1.5	61	1.9	73	13	5	78	31
80	2.0	2.1	81	2.5	97	17	7	105	41
100	2.5	2.6	102	3.1	122	22	9	131	51
120	3.0	3.1	122	3.7	147	26	10	157	62
150	3.8	3.9	153	4.7	183	33	13	196	77
200	5.1	5.2	204	6.2	245	44	17	261	103
300	7.6	7.8	306	9.3	368	65	26	392	154

(a) Screen size (diagonal)		16 : 9 screen							
		(b) Projection distance				(c) Screen height			
		min.		max.		down		up	
inch	m	m	inch	m	inch	cm	inch	cm	inch
60	1.5	1.7	66	2.0	79	2	1	73	29
80	2.0	2.2	88	2.7	106	2	1	97	38
100	2.5	2.8	111	3.4	133	3	1	122	48
120	3.0	3.4	133	4.1	160	3	1	146	58
150	3.8	4.2	166	5.1	200	4	2	183	72
200	5.1	5.6	222	6.8	267	5	2	243	96
300	7.6	8.5	334	10.2	400	8	3	365	144

Model No.VS11611

PROJECTOR	Type	0.63" (×3) Poly-Si TFT with micro-lens
	Pixel Format	1024×768 XGA
	Lens	Manual zoom, manual focus
	Zoom Factor	1.2
	Keystone	Vertical ±30°
DISPLAY	Size	30"-300" (Diagonal)
	Throw Distance	0.73- 7.91m
	Throw Ratio	1.3-1.5
	Lamp	160W
	Brightness	2,200 ANSI lumens
	Contrast Ratio	500:1
	Aspect Ratio	4:3 (native), 16:9
AUDIO	Speakers	1 watt×1
INPUT SIGNAL	Computer and Video	RGB analog, NTSC M, NTSC 4.43, PAL, SECAM
	Frequency	Fh:31.5-106 KHz ; Fv:56-120 Hz
COMPATIBILITY	PC	from VGA up to UXGA (scaled)
	Mac	up to SXGA (may require a Mac adapter)
CONNECTOR	RGB (input)	15-pin HD, D-sub cable (×2)
	Composite Video (input)	RCA jack (×1)
	S-Video (input)	Mini-Din 4-pin (×1)
	Audio (input)	RCA jack (×1 set), Stereo mini jack×1
	Audio (output)	Stereo mini jack
	USB	Type A for PC-Less Presentation (JEPG, MPEG4, M-JPEG) Type B for mouse contol
POWER	Voltage	100-240 VAC, 50/60Hz (universal)
	Consumption	250W (typ)
CONTROLS	Basic	Standby/On, input, menu
	Remote	Language, brightness, contrast, gamma, color temperature, color, tint, sharpness, progressive, My Memory, aspect, overscan, V./H. position, H. phase, H. size, auto adjust, color space, component, video format, frame lock, information, V. keystone, auto keystone, whisper, mirror, volume, audio, language, menu position, OSD bright, blank color, start up, My Screen, Pin Lock, My Screen Lock, message, auto search, auto off, lamp time, filter time, service menu, Security , USB storage, Auto on, Auto off
OPERATING CONDITION	Temperature	41℉ - 91℉（5℃ - 35℃）
	Humidity	10% - 90%（non-condensing）
NOISE LEVEL	Normal	36 dB (typ)
	Elo mode	30 dB (typ)
DIMENSIONS (W x D x H)	Physical (mm)	274mm×59mm×205mm
WEIGHT	Net	1.78 kg (3.9 lbs)
	Gross	4.5 kg (9.9 lbs)
REGULATIONS		UL 60950, C-UL, FCC-B, TUV/GS, CB, CE, C-TICK, NOM
PACKAGE CONTENTS		Projector, power cords, VGA cable, RCA video cable, remote control, AA Batteries, soft case, lens cap, ViewSonic Wizard CD, Quick Start Guide

Headquarters:
381 Brea Canyon Road,
Walnut, CA 97189, U.S.A.
salesinfo@viewsonic.com
www.viewsonic.com

Asia Pacific:
9F, No. 1 92 Lien Chien Road,
Chung Ho, Taipei, R.O.C.
www.viewsonic.com.tw

ViewSonic Hong Kong
Unit 3, 15/F, Greenfield Tower,
Concordia Plaza,
1 Science Museum Road, TST East,
Kowloon, Hong Kong
www.hk.viewsonic.com

ViewSonic (Singapore) Pte Ltd
Marine Parade Road #09-02
Parkway Parade
Singapore 449269
www.viewsonic.com.sg

ViewSonic Australia Pty Ltd
Unit 3, 44 Dickson Avenue,
Artarmon NSW 2064, Australia
www.viewsonic.com.au

ViewSonic Korea
#907, 9F, Hyundai HYEL, 2-36,
Hangangro 2-ga,
Yongsan-gu, Seoul, Korea 140-871
www.kr.viewsonic.com

ViewSonic Technologies (India) Pvt Ltd.
M-28, Commercial Complex (M-Block Market) 3rd floor,
Greater Kailash-II N Delhi - 110 048, India
in.viewsonic.com

ViewSonic® See the difference™